



GPS
NETWORKING

Contact us for product details and pricing

NavtechGPS

+1-703-256-8900 or 800-628-0885

info@NavtechGPS.com

www.NavtechGPS.com

L1/L2GRRKPA-N

GPS L1/L2/L5 Galileo/GLONASS

Passive GPS Antenna 2.6" Diameter, N-Female



General Specifications:

- Diameter = 2.60 in.
 - VSWR: 1.5:1 (max)
 - Frequencies 1535 - 1616 MHz (L1)
 - Polarization: Right Hand Circularly
- (Includes GPS L1/L6, GLONASS G1, Galileo L1/L6/E1/E2)
- Frequency 1164-1278.00 MHz (L2)
 - Impedance: 50 Ohms
- (Includes GPS L2/L5, GLONASS G2, Galileo E5a/E5b/E6)
- DC Grounding: Yes (lightening protection)
 - Temperature -55 to +85 C
 - L1/L2 Ceramic Patch Element = +3.0 dBic Max
 - Connector: N(f)
- Federal/Military Specifications: FAA TSO-C144, DO-160D, DO-228 MIL-C-5541, MIL-E-5400, MIL-I-45208A AND MIL-STD-810

NavtechGPS

Contact NavtechGPS for product details. www.NavtechGPS.com

+1-703-256-8900 • 800-628-0885 • info@navtechgps.com