



Antennas

Exceptional performance. Unsurpassed reliability.

NavtechGP5

+1-703-256-8900 or 800-628-0885 info@NavtechGPS.com www.NavtechGPS.com



Hexagon | NovAtel® Antennas

SIGNALS RECEIVED

		MODEL	GPS			GLONASS		
VEXXIS® GNSS-800 Series			L1	L2	L5	L1	L2	L3
		GNSS-802	+	+		+	+	
	Size: 179 x 55 mm Weight: 0.5 kg	GNSS-802L	+	+		+	+	
None None No.		GNSS-804	+	+		+	+	
		GNSS-804L	+	+		+	+	
		GNSS-850	+	+	+	+	+	+
VEXXIS® GNSS-500 Series								
	Size: 155 x 45 mm	GNSS-501	+			+		
Nouvited	Weight: 0.45 kg	GNSS-502	+	+		+	+	
Compact GNSS Antennas	'							
0	Size: 90 x 20 mm Weight: 0.20 kg	GPS-301	+					
	Size: 90 x 27 mm Weight: 0.35 kg	GNSS-303L	+	+	+	+	+	
		GNSS-302L-A	+	+		+	+	
	Size: 120 L x 80 W x 30 H mm Weight: 0.28 kg	GPS-302-A	+	+				
		GPS-302L-A	+	+				
		GNSS-303L-A	+	+	+	+	+	
Fixed Reference GNSS Antenna								
	Size: 380 × 200 mm Weight: 7.6 kg	GNSS-750	+	+	+	+	+	+
ii.	Size: 308 × 223 mm Weight: 4.1 kg	ANT-C2GA-TW-N	+	+				

SIGNALS RECEIVED

	Gal	ileo			BeiDou		L-Band	nd SPECIFICATIONS			
E1	E5a	E5b	E6	B1	B2	В3		LNA Gain	Power	RF Connector(s)	Compliance
+				+				29 dB typ	3.8 to 18 VDC, 60 mA max	TNC female	CE, FCC
+				+			+	29 dB typ	3.8 to 18 VDC, 60 mA max	TNC female	CE, FCC
+		+		+	+			29 dB typ	3.8 to 18 VDC, 60 mA max	TNC female	CE, FCC
+		+		+	+		+	29 dB typ	3.8 to 18 VDC, 60 mA max	TNC female	CE, FCC
+	+	+	+	+	+	+	+	29 dB typ	3.8 to 18 VDC, 60 mA max	TNC female	CE, FCC
+				+			+	29 dB typ	3.3 to 18 VDC, 20 mA typ	TNC female	CE, FCC
+		+		+	+		+	L1 34 dB, L2 38 dB	3.3 to 18 VDC, 20 mA typ	TNC female	CE, FCC
								26 dB typ	3.8 to 8 VDC, 35 mA typ	TNC male	CE, FCC
+	+	+	+	+	+	+	+	26 dB to 30 dB typ	3.8 to 6 VDC, 60 mA typ	TNC male	CE, FCC
							+	26 dB to 33 dB typ	3.8 to 6 VDC, 20 mA typ	TNC male	CE, FCC
								26 dB to 29 dB typ	3.8 to 6 VDC, 60 mA typ	TNC male	CE, FCC
							+	26 dB to 30 dB typ	3.8 to 6 VDC, 60 mA typ	TNC male	CE, FCC
+	+	+	+	+	+	+	+	26 dB to 30 dB typ	3.8 to 6 VDC, 60 mA typ	TNC male	CE, FCC
+	+	+	+	+	+	+	+	41 dB ± 3	3.3 to 12 VDC, 100 mA typ	N-Type with TNC adapter	CE, FCC
								L1 31 dB , L2 33 dB typ	2.5 to 24 VDC, 35 mA typ	TNC	CE, FCC



About Hexagon | NovAtel®

Hexagon is a global leader in sensor, software and autonomous solutions. We are putting data to work to boost efficiency, productivity, and quality across industrial, manufacturing, infrastructure, safety, and mobility applications. Our technologies are shaping urban and production ecosystems to become increasingly connected and autonomous — ensuring a scalable, sustainable future.

NovAtel, part of Hexagon, is a global technology leader, pioneering end-to-end solutions for assured positioning for land, sea, and air. NovAtel designs, manufactures and sells high precision positioning technology developed for efficient and rapid integration. Its solutions are empowering intelligent positioning ecosystems in vital industries that depend on the ability to tackle the most complex challenges in the most demanding environments. Learn more at novatel.com.

Hexagon (Nasdaq Stockholm: HEXA B) has approximately 20,000 employees in 50 countries and net sales of approximately 3.8bn EUR. Learn more at hexagon.com and follow us @HexagonAB.



©2020 Novatel Inc. All rights reserved. NovAtel is part of Hexagon. All trademarks or servicemarks used herein are property of their respective owners. NovAtel makes no representation or warranty regarding the accuracy of the information in this publication. This document gives only a general description of the product(s) or service(s) offered by NovAtel, and, except where expressly provided