Antennas GPS-704-X



MULTI-FREQUENCY ANTENNA DELIVERS EXCELLENT PERFORMANCE, MULTIPATH REJECTION AND L-BAND FUNCTIONALITY



EXCEPTIONAL L-BAND RECEPTION

The GPS-704-X Galileo passive antenna features improved performance to ensure excellent operation in all GPS, Galileo and GLONASS frequency bands. The antenna also includes NovAtel's patented Pinwheel® technology for excellent multipath rejection and phase center stability.

BENEFITS

+ Provides a single antenna solution for GPS L1, L2, L5, Galileo L1, E5a & b, E6, GLONASS L1, L2, BeiDou B1, B2, B3 and L-Band

FEATURES

+ Access to multiple Global Navigation Satellite Systems

If you require more information about our antennas, visit www.novatel.com/antennas

GPS-704-X

PERFORMANCE

3 dB Pass Band 1.15 - 1.65 GHz **Passive Antenna** External LNA Required **Gain at Zenith (90°)**

L1 +6.0 dBic (minimum)
L2, B2 +2.5 dBic (minimum)
L5, E5a +2.0 dBic (minimum)
E6, B3 +3.0 dBic (minimum)
L-Band, B1 +6.0 dBic (minimum)

Gain Roll-Off (from Zenith to Horizon)

PHYSICAL AND ELECTRICAL

Size

Diameter¹185 mmHeight69 mmWeight468 gConnectorTNC female

ENVIRONMENTAL

Temperature

Operating -40°C to +85°C
Storage -55°C to +85°C
Humidity 95% non-condensing
Salt Spray MIL-STD-810F, 509.4
Waterproof IEC 60529 IPX7
Compliance CE
ROHS EU Directive 2011/65/EU

For the most recent details of this product: www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas/gps-704-x/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-54452990-8011

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 4 Specifications subject to change without notice.

©2014 NovAtel Inc. All rights reserved.

NovAtel and Pinwheel are registered trademarks of NovAtel Inc.

Printed in Canada.

D09449 February 2014





