

PwrPak7D-E2

OEM7 Dual Antenna Enclosure With SPAN GNSS+INS Technology Provides Improved Performance And Higher Data Rates



Dual Antenna Input

Multi-frequency, dual antenna input allows the PwrPak7D-E2 to harness the power of RTK and ALIGN functionality. This makes the PwrPak7D-E2 ideal for ground, marine or aircraft based systems, providing industry-leading GNSS multi-constellation heading and position data in static and dynamic environments.

World Leading GNSS+INS Technology

SPAN GNSS+INS technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and Inertial Navigation System (INS). The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) gyro and accelerometer measurements are deeply coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

SPAN-Enabled MEMS Receiver

The PwrPak7D-E2 contains an Epson G370N MEMS IMU to deliver world class SPAN technology by Hexagon | NovAtel in an integrated, single box solution. Built on top of the reputable PwrPak7 family, with a higher performance Epson IMU, it provides seamless positioning, quick alignment and excellent performance. This product is commercially exportable and provides an excellent midrange price/performance/size GNSS+INS solution.

Future-Proofed Scalability

Capable of tracking all present and upcoming GNSS constellations and satellite signals, the PwrPak7D-E2 is a robust, high-precision receiver that is software upgradeable in the field to provide the custom performance required for your application demands.

The PwrPak7D-E2 has a powerful OEM7 GNSS engine, integrated MEMS IMU, built in Wi-Fi, onboard NTRIP client and server support, and 16 GB of internal storage.

Precise Thinking Makes It Possible

Our GNSS products have set the standard in quality and performance for over 20 years. State-of-the-art, lean manufacturing facilities in our North American headquarters produce the industry's most extensive line of OEM receivers, antennas and subsystems.

Benefits

- Small, low-power, all-in-one GNSS+INS enclosure
- Easy integration into space and weight constrained applications
- Commercially exportable system
- Rugged design ideal for challenging environments
- Enhanced connection options including serial, USB, CAN and Ethernet
- Future-proof for upcoming GNSS signal support

Features

- Low noise commercial grade Gyros and Accelerometers
- Dedicated Wheel Sensor input
- TerraStar correction services supported over multi-channel L-Band and IP connections
- Advanced interference mitigation features
- SPAN GNSS+INS capability with configurable application profiles
- Dual antenna ALIGN heading
- 16 GB of internal storage
- Built-in Wi-Fi support

Performance¹**Signal Tracking²**

GPS	L1 C/A, L1C, L2C, L2P, L5
GLONASS ³	L1 C/A, L2 C/A, L2P, L3, L5
Galileo ⁴	E1, E5 AltBOC, E5a, E5b
BeiDou	B1I, B1C, B2I, B2a, B2b
QZSS	L1 C/A, L1C, L2C, L5
NavIC (IRNSS)	L5
SBAS ⁵	L1, L5
L-Band ⁵	up to 5 channels

Horizontal Position Accuracy (RMS)

Single Point L1	1.5 m
Single Point L1/L2	1.2 m
SBAS ⁶	60 cm
DGPS	40 cm
TerraStar-L ⁷	40 cm
TerraStar-C PRO ⁷	2.5 cm
TerraStar-X ⁷	2 cm
RTK	1cm+1ppm
Initialization time	< 10 s
Initialization reliability	> 99.9%

ALIGN Heading Accuracy

Baseline	Accuracy (RMS)
2 m	0.08 deg
4 m	0.05 deg

Maximum Data Rate

GNSS Measurements	up to 20 Hz
GNSS Position	up to 20 Hz
INS Solution	up to 200 Hz
IMU Raw Data Rate	200 Hz

Time to First Fix

Cold start ⁸	< 39 s (typ)
Hot start ⁹	< 20 s (typ)

Time Accuracy¹⁰ 20 ns RMS**Velocity Limit¹¹** 515 m/s**IMU Performance¹²****Gyroscope Performance**

Input range	±450 deg/s
Rate bias stability	0.8 deg/hr
Angular random walk	0.06 deg/√hr

Accelerometer Performance

Range	±10 g
Bias stability	0.01 mg
Velocity random walk	0.025 m/s/√hr

Communication Ports

1 RS-232	up to 460,800 bps
2 RS-232/RS-422 selectable	
	up to 460,800 bps
1 USB 2.0 (device)	HS
1 USB 2.0 (host)	HS
1 Ethernet	10/100 Mbps
1 CAN Bus	1 Mbps
1 Wi-Fi	
3 Event inputs	
3 Event outputs	
1 Pulse Per Second output	
1 Quadrature Wheel Sensor input	

Physical and Electrical**Dimensions** 147 x 125 x 55 mm**Weight** 560 g**Power**

Input voltage	+9 to +36 VDC
Power consumption ¹³	4.15 W

2 Antenna LNA Power Outputs

Output voltage	5 VDC ±5%
Maximum current	200 mA

Connectors

2 Antenna	SMA
USB device	Micro A/B
USB host	Micro A/B
Serial, CAN, Event I/O	DSUB HD26
Ethernet	RJ45
Data Logging	Push button
Power	SAL M12, 5 pin, male

Status LEDs

Power
GNSS
INS
Data Logging
USB

Environmental**Temperature**

Operating	-40°C to +75°C
Storage	-40°C to +85°C

Humidity 95% non-condensing**Ingress Protection Rating** IP67**Vibration (operating)**

Random	MIL-STD-810H, Method 514.8
Profiles:	

- Rail CAT 11 – 0.5 g RMS
- Composite Wheeled Vehicle CAT 4 – 2.24 g RMS
- Aircraft Propeller CAT 13 – 4.5 g RMS

Acceleration (operating)MIL-STD-810H, Method 513.8
Procedure II (16 g)**Bump (operating)**

IEC 60068-2-27 (25g)

Shock (operating)¹⁴MIL-STD-810H,
Method 516.8, Procedure 1,
40 g 11 ms terminal sawtooth**Compliance**FCC, ISED, CE and
Global Type Approvals**Included Accessories**

- Power cable
- USB cable
- DSUB HD26 to DB9 RS-232 cable

Optional Accessories

- Full breakout cable for DSUB HD26 connector
- DSUB HD26 to M12 IMU cable
- RJ45 Ethernet cable
- VEXXIS GNSS-500 and GNSS-800 series antennas
- Compact GNSS antennas
- GrafNav/GrafNet
- Inertial Explorer
- NovAtel Application Suite

Hardware Options

PwrPak7DQ-E2 no Wi-Fi

Performance During GNSS Outages¹

Outage Duration	Positioning Mode	Position Accuracy (M) RMS		Velocity Accuracy (M/S) RMS		Attitude Accuracy (Degrees) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK ¹⁵	0.02	0.03	0.015	0.010	0.013	0.013	0.070
	PPP	0.06	0.15					
	SP	1.00	0.60					
	Post Processed ¹⁶	0.01	0.02					
10 s	RTK ¹⁵	0.17	0.13	0.040	0.020	0.022	0.022	0.085
	PPP	0.21	0.25					
	SP	1.15	0.70					
	Post Processed ¹⁶	0.02	0.02					
60 s	RTK ¹⁵	5.02	1.03	0.220	0.035	0.035	0.035	0.120
	PPP	5.06	1.15					
	SP	6.00	1.60					
	Post Processed ¹⁶	0.17	0.06					

1. Typical values. Performance specifications subject to GNSS system characteristics, Signal-in-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference. 2. Model-configurable to track L5/E5a (all / Galileo) through L2 (GPS) or L3/E5b/B2 (GLONASS / Galileo / BeiDou) through L2 (GLONASS). See manual for details. 3. Hardware ready for L3 and L5. 4. E1bc and E5bc support only. 5. L-Band and SBAS reception on primary antenna only. 6. GPS-only. 7. Requires a subscription to a TerraStar data service. Subscriptions available from NovAtel. 8. Typical value. No almanac or ephemerides and no approximate position or time. 9. Typical value. Almanac and recent ephemerides saved and approximate position and time entered. 10. Time accuracy does not include biases due to RF or antenna delay. 11. Export licensing restricts operation to a maximum of 515 meters per second, message output impacted above 500 m/s. 12. Supplied by IMU manufacturer. 13. Typical values using serial port communication without interference mitigation. Consult the OEM7 User Documentation for power supply considerations. 14. GNSS only. IMU measurements may not be valid. 15. 1ppm should be added to all position values to account for additional error due to baseline length. 16. Post-processing results using Inertial Explorer software. The survey data used to generate these statistics had frequent changes in azimuth.



Contact NavtechGPS for product details. www.NavtechGPS.com
+1-703-256-8900 • 800-628-0885 • info@navtechgps.com