

Product Highlight

TW3710 / TW3712 Single Band GNSS Antenna



TALLYSMAN®

When precision matters.®

TW3710 / TW3712 Single Band GNSS Antenna

Frequency Coverage: L1/G1/E1/B1

The TW3710 /TW3712 employs Tallysman's unique Accutenna® technology covering the BeiDou B1, Galileo E1, GPS L1, GLONASS G1 and SBAS (WAAS, QZSS, EGNOS & MSAS) frequency band (1557 to 1606 MHz). It provides truly circular response over its entire bandwidth thereby producing superior multipath signal rejection. It is especially suitable for high accuracy applications, and also offers high out of band signal rejection.

Both antennas feature a dual-feed wideband patch element, with a two stage Low Noise Amplifier, comprised of one input LNA per feed, a mid section SAW to filter the combined output, and a final output gain stage. This configuration provides excellent axial ratio that is constant across the full frequency band along with a superb phase linear response and tight phase centre variation providing performance normally associated with much higher priced antennas.

The TW3712 has a pre-filter to protect against front end saturation by strong near frequency or harmonic signals.

The antennas are housed in a through-hole mount, weatherproof enclosure for permanent installations. L Bracket or Pipe Mount adapters (part numbers 23-0040-0, 23-0065-0 respectively) are available for non-rooftop installation. A 100mm ground plane is recommended for non-roof-top installations.



Applications

- High Accuracy & Mission Critical Global Positioning
- Precision Agriculture, Mining & Construction
- Military & Security
- Avionics
- Law Enforcement & Public Safety
- Fleet Management & Asset Tracking

Features

- Covers all GNSS Frequencies
- Great axial ratio: 1 dB typ.
- Low noise LNA: 1 dB (TW3710)
- High rejection SAW filter
- High gain LNA: 28 dB typ. (TW3710)
- Low current: 15 mA typ.
- Wide voltage input range: 2.5 to 16 VDC

Benefits

- Excellent circular polarisation
- Excellent multipath rejection
- Excellent signal to noise ratio
- Great out of band signal rejection
- Increased system accuracy
- Ideal for harsh environments
- RoHS and REACH compliant



Contact NavtechGPS for product details. www.NavtechGPS.com
+1-703-256-8900 • 800-628-0885 • info@navtechgps.com

Product Highlight

TW3710 / TW3712 Single Band GNSS Antenna

Product Information

Model	Mounting	Frequencies	Amplifier Gain
TW3710 / TW3712	Through-Hole	L1/G1/E1/B1	28 dB typ.

Remarks: TW3712 Prefiltered

Learn More: [TW3710](#) / [TW3712](#)

[TW3710 / TW3712 Datasheet](#)

Ordering Information

TW3710 – Single Band GNSS antenna 33-3710-xx-yy-zzzz

TW3712 – Pre-filtered Single Band GNSS antenna 33-3712-xx-yy-zzzz

Where xx = connector type, yy = shape and colour of radome and zzzz = cable length in mm (where applicable)

Related Information

- [Tallysman Antenna Selection Guide](#) – Finding the right antenna for your application
- [Tallysman Ordering Guide](#) – View the wide range of “standard” customizations for Tallysman’s entire antenna line



Contact NavtechGPS for product details. www.NavtechGPS.com
+1-703-256-8900 • 800-628-0885 • info@navtechgps.com

© 2019 Tallysman Inc. All rights reserved. Tallysman, the “When Precision Matters” tag line and the Tallysman logo are trademarks or registered trademarks of Tallysman Inc. and/or its affiliates in Canada and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. The information presented is subject to change without notice. Tallysman assumes no responsibility or any errors or omissions in this document. Tallysman Wireless Inc. hereby disclaims any or all warranties and liabilities of any kind.

Contact us:
info@tallysman.com
T: +1 613 591-3131