

### KEY FEATURES

Comprehensive GNSS support, including GPS Modernization signals, GLONASS, BeiDou and Galileo

Robust low-elevation satellite tracking

Minimized multipath

Sub-millimeter phase center repeatability

Ideal for fixed reference stations and GNSS infrastructure networks



ZEPHYR 2 ANTENNA



ZEPHYR 2 RUGGED ANTENNA



ZEPHYR 2 GEODETIC ANTENNA

### TRIMBLE ZEPHYR ANTENNAS

The top of the range Trimble® Zephyr™ external GNSS antenna contains advanced technology for multipath reduction, outstanding low elevation satellite tracking, and sub-millimeter phase center stability. The Trimble Zephyr 2, Zephyr 2 Rugged, and Zephyr 2 Geodetic antennas offer full support for current and near-future GNSS signals in combination with the rugged durability of each antenna, means the investment in a Trimble Zephyr series antenna will last for many years.

#### TRIMBLE ZEPHYR 2

The Trimble Zephyr 2 is a high-performance lightweight GNSS rover antenna optimized for precision RTK applications. The Zephyr 2 GNSS antenna is typically used in roving applications. It minimizes multipath, and offers robust low elevation tracking and sub-millimeter phase center repeatability.

#### TRIMBLE ZEPHYR 2 RUGGED

The Trimble Zephyr 2 Rugged Antenna is intended for installations subject to high shock and vibration on the job site. Ideal for drilling rigs, marine vessels, cranes and other vehicle applications, it offers precise positioning with sub-millimeter phase center accuracy.

Key features of the Zephyr 2 and Zephyr 2 Rugged:

- Optimized for GNSS rover applications
- Robust low-elevation satellite tracking
- Minimized multipath
- Sub-millimeter phase center repeatability

#### TRIMBLE ZEPHYR 2 GEODETIC

The Trimble Zephyr 2 Geodetic antenna is extremely rugged and ideal for control work. The Zephyr 2 Geodetic is recommended for all base station applications. This antenna is also suitable as a fixed rover antenna for use in high multi-path environments.

The Zephyr 2 Geodetic antenna's quality performance and extreme accuracy are achieved through sub-millimeter phase center repeatability, robust low-elevation tracking and significantly reduced ground-based multipath.

Key features:

- Optimized for GNSS base station applications
- Robust low-elevation satellite tracking
- Large ground plane for best multipath rejection
- Sub-millimeter phase center repeatability
- Ideal for fixed reference stations and GNSS infrastructure networks

#### COMPREHENSIVE GNSS SUPPORT

The Trimble Zephyr 2 antennas have the ability to track Modernized GPS signals, GLONASS, Galileo, BeiDou, OmniSTAR, and SBAS, the Zephyr 2 antennas are an excellent investment for the future.



# TRIMBLE ZEPHYR ANTENNAS

## PERFORMANCE

### ZEPHYR 2, ZEPHYR 2 RUGGED AND ZEPHYR 2 GEODETIC ANTENNAS

- Broad GNSS Frequency Tracking Band Including:
  - GPS: L1, L2, L5
  - GLONASS: L1, L2, L3
  - BeiDou: B1, B2, B3
  - Galileo: E1, E2, E5, E6
  - SBAS: WAAS, EGNOS, QZSS, Gagan, MSAS, and OmniStar
- Quality signal tracking, even below 5 degrees elevation
- Four point antenna feed for phase center stability and enhanced polarization
- TNC female signal connector
- Small cross-sectional area to reduce wind loading
- 13 dB amplifier margin supports cable runs of over 60 m without special coaxial cable or in-line amplifiers
- North orientation marking on exterior
- 50 dB signal gain for reliable tracking in difficult environments
- Low voltage, low power consumption
- Integral low noise amplifier
- 5/8" x 11 female threaded stainless steel mount point
- Powered by GNSS receiver via coaxial cable
- Advanced LNA (low noise amplifier) to reduce jamming by high power out-of-band transmitters

### ZEPHYR 2 GEODETIC ANTENNA ONLY

- Trimble Stealth Ground Plane – integrated lightweight stealth technology with enhanced right hand circular polarization to reduce multipath interference
- Supplementary radome not required (available if desired)

## HARDWARE

### Dimensions

Zephyr 2	16.5 cm diameter x 7.6 cm height (6.5 in diameter x 3 in height)
Zephyr 2 Rugged	25.4 cm diameter x 11.1 cm height (10" diameter x 4.37" height)
Zephyr Geodetic 2	34.3 cm diameter x 7.6 cm height (13.5 in diameter x 3 in height)

### Weight

Zephyr 2	0.64 kg (1.4 lb)
Zephyr 2 Rugged	1.8 kg (4 lb)
Zephyr Geodetic 2	1.36 kg (3 lb)

## ENVIRONMENTAL

Operating Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Humidity	100% humidity proof, fully sealed
Input Voltage	3.5 V DC to 20 V DC
Input Current	125 mA maximum
Shock and Vibration	Tested and meets the following environmental standards

### Zephyr 2 and Zephyr 2 Geodetic

Shock	MIL-STD-810-F to survive a 2 m (6.56 ft) drop onto concrete
Vibration	MIL-STD-810-F on each axis
Zephyr 2 Rugged	
Shock	5 Gs, 6 ms duration, 3 shocks in mutually perpendicular axis
Vibration	Vibration: 20.4 gRMS. Bouyant

For more information contact



Your ONE Source for GNSS Products and Solutions

+1-703-256-8900 or 800-628-0885  
 info@NavtechGPS.com  
 www.NavtechGPS.com

Specifications subject to change without notice.

© 2014, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. (01114)



**AMERICAS**  
**TRIMBLE NAVIGATION LIMITED**  
 Integrated Technologies  
 510 DeGuigne Drive  
 Sunnyvale, CA 94085 USA  
 +1-408-481-8070 Phone  
 +1-408-481-8984 Fax  
 Email: americasales@trimble.com

**EUROPE & MIDDLE EAST**  
**TRIMBLE GERMANY GmbH**  
 Integrated Technologies  
 Am Prime Parc 11  
 65479 Raunheim, Germany  
 +49 (6142) 177-2135 Phone  
 +49 (6142) 177-2136 Fax  
 Email: emeasales-intech@trimble.com

**CHINA**  
**TRIMBLE NAVIGATION LIMITED**  
 Integrated Technologies  
 311 Fute (M) Road, 3F  
 Wai Gaoqiao Free Trade Zone  
 Pudong, Shanghai 200131 China  
 Email: chinasales-intech@trimble.com

**ASIA - PACIFIC**  
**TRIMBLE NAVIGATION LIMITED**  
 Integrated Technologies  
 Email: asiasales-intech@trimble.com

**RUSSIA**  
**TRIMBLE NAVIGATION LIMITED**  
 Integrated Technologies  
 +49 (6142) 177-2135 Phone  
 Email: rusasales-intech@trimble.com