

# PLUS RADIOS

## FGR2 ETHERNET 900 MHZ

### INDUSTRIAL RADIO



**FREEWAVE**

Contact us for product details and pricing

**NavtechGPS**

+1-703-256-8900 or 800-628-0885

info@NavtechGPS.com

www.NavtechGPS.com



## KEY FEATURES

### **Outstanding RF Performance:**

Maintains high receiver sensitivity and noise immunity even in harsh RF conditions

**High Speed:** Up to 154 kbps over-the-air throughput

**Secure:** Frequency Hopping Spread Spectrum (FHSS) technology and AES encryption prevent unauthorized access

### **Synthesized Waveform Transmit**

**Data:** Reduces out-of-band modulation products

**Error Free Communications:** 32 bit CRC with automatic retransmission

**Versatile:** Operates as a Gateway, Repeater or End Point

**Backward Compatible:** 100% compatible with all existing 900 MHz FreeWave FGRPlus radios

**Input Voltage Range:** +6 to +30 VDC  
UL Approved: Class 1 Division 2

## OVERVIEW

The FGR2-PE and FGR2-P offer Ethernet and serial data communications using 900MHz license-free spectrum for reliable connectivity in RF harsh environments and over long data links. Both FGR2 Ethernet radios offer two 10/100 Ethernet ports as well as two serial ports, and industrial grade AES encryption to meet the demands of wireless automation. This future-proof combination of serial and switched Ethernet ports are fully compatible with the FGRPlus family of radios and allow for the transition from serial to Ethernet communications without having to replace existing wireless communication infrastructure. The flexibility and cost effectiveness of the FGR2 Ethernet line also reduces the need for additional radio inventory since all radio can be programmed to operate as Gateways, Repeaters and End Points.

All radios are designed, manufactured and tested in Boulder, CO.

# TECHNICAL SPECIFICATIONS

## SPECIFICATIONS

FGR2-PE	6.8 L x 3.8 W x 1.4 H (in) Enclosed
FGR2-PE-U	6.8 L x 3.8 W x 1.4 H (in) Enclosed
FGR2-P	7 L x 3.25 W x 1.25 H (in) Board Level

## TRANSMITTER

Frequency Range	902 to 928 MHz (FHSS)
Output Power	5 mW to 1 W
Data Link Range	60 miles, clear line of sight
Modulation	2 level GFSK
RF Data Rate	115.2 kbps standard speed 153.6 kbps high speed
Occupied Bandwidth	230.4 kHz
Hopping Patterns	15 per band, 105 total, user-selectable
Hopping Channels	112
Frequency Zones	16 zones, 7-8 channels per zone

## RECEIVER

Sensitivity	-108 dBm, at standard speed, $1 \times 10^{-6}$ BER -104 dBm, high speed, $1 \times 10^{-6}$ BER
-------------	-----------------------------------------------------------------------------------------------------

## DATA TRANSMISSION

Error Detection	32 bit CRC, retransmit on error
Data Security	AES 128 bit encryption FHSS technology RADIUS
Serial Interface	RS232/RS422/RS485, programmable (2) RJ-45 connectors
Ethernet Interface	802.3, IPv4, TCP, UDP, DHCP, ICMP, ARP, Multicast, TFTP, DNP3 over TCP (2) 802.3u, Fast Ethernet, RJ-45

## POWER REQUIREMENTS

Operating Voltage	+6 VDC to +30 VDC
Typical Power	Transmit: 6.6 W Receive: 1.8 W Idle: 0.8 W

## GENERAL INFORMATION

Operating Temperature	-40°C to +75°C
Humidity	0 to 95%, non-condensing
Dimensions	Board Level: 178 x 83 x 32 (mm) Enclosed: 173 x 97 x 36 (mm)
Weight	Board Level: 227 g Enclosed: 635 g
Antenna Connector	Board Level: SMA, female Enclosed: TNC, female
Certifications	FCC Part 15.247 / IC RSS-210 UL Class 1, Division 2



Contact NavtechGPS for product details. [www.NavtechGPS.com](http://www.NavtechGPS.com)  
+1-703-256-8900 • 800-628-0885 • [info@navtechgps.com](mailto:info@navtechgps.com)

## APPLICATIONS



OIL & GAS



AGRICULTURE



UTILITIES



DEFENSE



SCADA



MINING



FLEET  
MANAGEMENT



MUNICIPAL



ENTERPRISE

## CONTACT US

5395 Pearl Parkway, Boulder, CO 80301  
TF 866.923.6168 T 303.381.9200  
For more information, visit [www.freewave.com](http://www.freewave.com)